

# TEMPORARY REVISION

## AMM-TR-MÄM 42-1298

### Update of Propeller Governor RPM

This Temporary Revision AMM-TR-MÄM 42-1298 is approved in conjunction with the Mandatory Design Change Advisory MÄM 42-1298 and is valid in conjunction with the Airplane Maintenance Manual (AMM) until this Temporary Revision has been incorporated into the AMM, latest revision.

The limitations and information contained herein either supplement or, in the case of conflict, override those in the AMM.

The technical information contained in this document has been approved under the authority of DOA No. EASA.21J.052.

Doc. No.	Section	Affected Pages
7.02.15	61-20-00	5a, 5aa

#### Instruction

- Print this document double-sided on yellow paper (odd pages and "a" pages on front sides, even pages and "aa" pages on reverse sides).
- Insert this cover page as the first page of the AMM.
- Insert the other pages of this Temporary Revision in front of the corresponding AMM pages.



Intentionally left blank

**AFFECTED CHAPTER:****CHAPTER 61**  
**PROPELLER**  
**Section 61-20-00**  
**Propeller Control****2. Description and Operation**

*The following items are amended to read:*

The specified propeller settings are given as follows:

– Max. revolution: 2680 RPM + 20 RPM

– Min. revolution: 1980 RPM ± 10 RPM

If MÄM 42-600 is installed:

– Max. revolution: 2680 RPM + 20 RPM

– Min. revolution: 1980 RPM ± 10 RPM

Intentionally left blank