

## TEMPORARY REVISION

### TR-MÄM-20-334

### Performance Data

This Temporary Revision TR-MÄM-20-334 is approved in conjunction with the Mandatory Design Change Advisory MÄM 20-334 and is valid in conjunction with the latest revision of the DV 20-100 Airplane Flight Manual until this temporary revision has been incorporated into the Airplane Flight Manual.

The limitations and information contained herein either supplement or, in the case of conflict, override those in the Airplane Flight Manual.

The technical information contained in this document has been approved under the authority of DOA No. EASA.21J.052.

Doc. No.	Section	Affected Pages
4.01.20-E	5	5-10a

#### **Instruction:**

- Print this document on yellow paper (single-sided).
- Insert this cover page as the first page of the AFM.
- Insert the other pages of this Temporary Revision in front of the corresponding AFM pages.

Doc. No. 4.01.20-E	TR-MÄM-20-334	11-Nov-2010	Cover page
--------------------	---------------	-------------	------------

**Affected Chapters:****5.3 PERFORMANCE TABLES AND DIAGRAMS****5.3.7 FIGURE 5.7: Climb Performance / Cruising Altitudes**

*The following NOTE is added after the Figure and the Example:*

**NOTE**

The steady rate of climb with take-off power in take-off configuration and  $v_y$  is 4.61 m/s (907 ft/min) at MSL and ISA conditions.