

Flugzeugbau – Friesach Ges. m. b. H. A-9322 Hirt/Friesach Telefon (0 42 68) 31 18 Telex 42 887

## SERVICE BULLETIN No. 9 E

Aircraft affected:

Motorglider H 36 "DIMONA" up to SNo's 36143 and 3539

5 1 15 4224 5

Subject:

Type certification in accordance with the Airworthiness requirements for Gliders and Motorgliders, JAR 22, dated 15.3.1982 and increase of the maximum Gross weight from

740 up to 770 kg.

Occasion:

As the result of a supplementary type examination the type has been approved in accordance with the spetifications mentioned above. The maximum Gross weight has been increased up to 770 kg. So, a higher payload is practicable after execution of this S.B.

Required actions:

- Replace Flight manual by Flight manual dated May 1984
- Replace Maintenance manual by Maintenance manual dated May 1984
- Attach modified placards according to the particulars on page 4 of this S.B.
- 4. Modify the Airspeed Indicator markings according to the particulars on page 3 of this S.B.
- 5. Transfer Datas from page 40 of the old Flight manual to page 43 of the new Flight manual, except the maximum payload.

Ascertain the new maximum payload and entry on page 43. Consider, that neither the maximum Gross weight of 770 kg nor the maximum weight of non-lifting-parts of 560 kg will be exceeded.

Compliance:

Not later than next annual inspection

Weight and balance:

The Center-of-gravity range modifies at air-born-weights above 740 kg (see Flight manual dated May 1984, pages 13 and 39). The maximum Gross weight increases up to 770 kg.

Notes:

The required actions of this S.B. must be carried—out by a competent person. The regular execution of the actions must be confirmed in the log book by an authorized aircraft maintenance engineer.

Flight— and Maintenance manuals as well as modified placards are available at the manufacturer or at: Hoffmann Flugzeugbau KG, Am Sportflugplatz, D-8870 Günzburg.


As a result of the increased Gross weight, the limitations and performances of the motorglider will change. The reading of the Flight manual by the pilot is required. Modified items are marked by vertical lines at the right margin.

The German issue of this S.B. is BAZ approved.

Hirt, 19.7.1984

(Dipl.-Ing. D. Oppel)

## Airspeed Indicator Markings



Green arc: 78 km/h - 210 km/h (42 kt - 113 kt) Yellow arc: 210 km/h - 275 km/h (113 kt - 148 kt) Red radial line at 275 km/h (148 kt) Blue radial line and yellow triangle at 95 km/h (51 kt) The following Placards must be attached/exchanged:

Data Plate and Loading Placard: (Below Canopy Frame left Side)

Airspeed Limits	•	*********		
Never Exceed v <sub>NE</sub>	:	275	149	170
Rough Air v <sub>B</sub>	:	210	113	1 30
Manoeuvring $v_{ extsf{A}}$	:	176	95	109
Max. Gross Weight min. Payload (in	:	770	kg 16	98 lbs
pilots seat) max. Payload (in	:	70	kg 1	54 lbs
any seat)	:	110	ka o	40 150
Baggage maximum	:		kg 2 kg	200
max. Payload: see			•	ar-case seventence

Next to battery storage:

Before removing battery insulate Rudder cable

Below canopy frame left side:

Approved aerobatic manoeuvres:
 Inside loop
 Vertical Turn
 Spin
 Lazy eight