



SUPPLEMENT NO. 11

TO THE AIRPLANE FLIGHT MANUAL FOR THE POWERED SAILPLANE HK 36 TS

ADDITIONAL PERFORMANCE DATA

Doc. No. : 3.01.06
Date of Issue : 10 Nov 1999

Pages identified by "ACG-appr." in the List of Effective Pages are approved by:

Signature : _____

Windler



Authority : _____

AUSTRO CONTROL GmbH
Abteilung Flugtechnik
Außenstelle Ost

Stamp : _____

A-1300 Wien-Flughafen, Hangar 2

Original date of approval : _____

12. Nov. 1999

This powered sailplane must be operated in compliance with the information and limitations contained herein.

Prior to operating the powered sailplane, the pilot must take notice of all the information contained in this Airplane Flight Manual.

DIAMOND AIRCRAFT INDUSTRIES GMBH
N.A. OTTO-STR. 5
A-2700 WIENER NEUSTADT
AUSTRIA / EUROPE

0.1 RECORD OF REVISIONS

Rev No.	Sec.	Pages	Date of Revision	Approval	Date of Approval	Date Inserted	Signature

Doc. No. 3.01.06-E	Issue 10 Nov 1999	Rev. No.	Date	Source	Page No. 9 - 11 - 1
-----------------------	----------------------	----------	------	--------	------------------------

0.2 LIST OF EFFECTIVE PAGES

Section	Pages	Date
0	9 - 11 - 1 9 - 11 - 2 9 - 11 - 3	10 Nov 1999 10 Nov 1999 10 Nov 1999
1, 2	9 - 11 - 4	10 Nov 1999
3, 4	9 - 11 - 5	10 Nov 1999
5	ACG-appr. 9 - 11 - 6 9 - 11 - 7	10 Nov 1999 10 Nov 1999
6, 7	9 - 11 - 8	10 Nov 1999
8	9 - 11 - 9	10 Nov 1999

Doc. No.	Issue	Rev. No.	Date	Source	Page No.
3.01.06-E	10 Nov 1999				9 - 11 - 2

0.3 TABLE OF CONTENTS

0.1 RECORD OF REVISIONS 9-11-1
 0.2 LIST OF EFFECTIVE PAGES 9-11-2
 0.3 TABLE OF CONTENTS 9-11-3

SECTION 1. GENERAL

1.1 INTRODUCTION 9-11-4

SECTION 2. LIMITATIONS

2.2 GENERAL 9-11-4

SECTION 3. EMERGENCY PROCEDURES

3.7 ENGINE FAILURE 9-11-5

SECTION 4. NORMAL PROCEDURES

4.1 GENERAL 9-11-5

SECTION 5. PERFORMANCE

5.3 ADDITIONAL INFORMATION 9-11-6

SECTION 6. MASS (WEIGHT) AND BALANCE / EQUIPMENT LIST

6.1 GENERAL 9-11-8

SECTION 7. POWERED SAILPLANE AND SYSTEMS DESCRIPTION

7.1 GENERAL 9-11-8

SECTION 8. POWERED SAILPLANE HANDLING, CARE AND MAINTENANCE

8.1 GENERAL 9-11-9

Doc. No.	Issue	Rev. No.	Date	Source	Page No.
3.01.06-E	10 Nov 1999				9 - 11 - 3

SECTION 1

GENERAL

1.1 INTRODUCTION

Pages 9-11-0 through 9-11-9 constitute Supplement No. 11 to the Airplane Flight Manual for the powered sailplane HK 36 TS.

This Supplement provides additional performance data as required by national authorities.

SECTION 2

LIMITATIONS

2.1 GENERAL

Section 2 remains unchanged.

Doc. No.	Issue	Rev. No.	Date	Source	Page No.
3.01.06-E	10 Nov 1999				9 - 11 - 4

SECTION 3

EMERGENCY PROCEDURES

3.1 GENERAL

Section 3 remains unchanged.

SECTION 4

NORMAL PROCEDURES

4.1 GENERAL

Section 4 remains unchanged.

Doc. No.	Issue	Rev. No.	Date	Source	Page No.
3.01.06-E	10 Nov 1999				9 - 11 - 5

SECTION 5

PERFORMANCE

5.3 ADDITIONAL INFORMATION

5.2.8 LANDING PERFORMANCE

WARNING

The given data does not include any safety reserves. For a safe landing, the available length of the runway must at least be equal to the landing distance over a 15 m (50 ft.) obstacle (l_2).

Under unfavorable conditions such as rain, tailwind, wind shear, sloped field, wet grass, a bad maintenance condition of the airplane or deviation from the given procedures, the landing distance can become considerably extended.

Under very unfavorable conditions, a safe landing can become impossible.

The given data were determined under the following conditions:

- Maximum take-off mass (weight)
- Power: Idle
- Propeller setting TAKE-OFF
- Approach speed appr. 105 km/h (57 kts. / 65 mph)
- Level, paved runway
- Brake flaps extended

The landing performance at MSL under ISA conditions is:

195m (640 ft.) landing roll and

395m (1296 ft.) landing distance over a 15 m (50 ft.) obstacle.

Doc. No.	Issue	Rev. No.	Date	Source	Page No.
3.01.06-E	10 Nov 1999				9 - 11 - 6

The landing distances are contained in the following tables:

l_1 = Landing roll

l_2 = Landing distance over a 15 m (50 ft.) obstacle

OAT [°C]	Pressure altitude above MSL [m] / QFE [hPa]							
	0 / 1013		400 / 966		800 / 921		1200 / 877	
	s_1 [m]	s_2 [m]	s_1 [m]	s_2 [m]	s_1 [m]	s_2 [m]	s_1 [m]	s_2 [m]
0	185	375	194	393	203	411	213	432
15	195	395	205	414	214	434	225	456
30	205	415	216	435	225	457	237	489

OAT [°F]	Pressure altitude above MSL [ft.] / QFE [inHg]							
	0 / 29.9		1310 / 28.5		2620 / 27.2		3940 / 25.9	
	s_1 [ft.]	s_2 [ft.]	s_1 [ft.]	s_2 [ft.]	s_1 [ft.]	s_2 [ft.]	s_1 [ft.]	s_2 [ft.]
32	607	1230	636	1289	666	1348	699	1417
59	640	1296	673	1358	702	1424	738	1496
86	673	1362	709	1427	738	1499	778	1604

Doc. No. 3.01.06-E	Issue 10 Nov 1999	Rev. No.	Date	Source	Page No. 9 - 11 - 7
-----------------------	----------------------	----------	------	--------	------------------------

SECTION 6

MASS (WEIGHT) AND BALANCE / EQUIPMENT LIST

6.1 GENERAL

Section 6 remains unchanged.

SECTION 7

POWERED SAILPLANE AND SYSTEMS DESCRIPTION

7.1 GENERAL

Section 7 remains unchanged.

Doc. No.	Issue	Rev. No.	Date	Source	Page No.
3.01.06-E	10 Nov 1999				9 - 11 - 8

SECTION 8

POWERED SAILPLANE HANDLING, CARE AND MAINTENANCE

8.1 GENERAL

Section 8 remains unchanged.

Doc. No.	Issue	Rev. No.	Date	Source	Page No.
3.01.06-E	10 Nov 1999				9 - 11 - 9